

m o o o i

The Party Wall Lamp

KRANEN/GILLE



'The Party' is inspired by a clan of strong, captivating personalities. Their casted ceramic faces bring to light our fascination with secrets, family dynamics and intrigue. If seen together, as a splendid party, they brighten up the stage with their cool playfulness. Yet behind the lamps' composed façades a mischievous side seeps through and touches our imagination.

Detailing



The lamps share the same basic tactile feel, a subtle roughness given by the granular ceramic finish, but are distinguished by their individual style.

Colours



Grey

The Party Wall Lamp / Bert

Dimensions

16cm | 6.3"



11cm | 4.3"
22cm | 8.7"



Product

WIDTH 16cm | 6.3"
HEIGHT 22cm | 8.7"
DEPTH 11cm | 4.3"
WEIGHT NETTO 0.5kg | 1.1lbs

Packaging

WIDTH 31.5cm | 12.4"
HEIGHT 31.5cm | 12.4"
CUBAGE 0.02m³ | 0.72ft³
LENGTH 20.5cm | 8.1"
WEIGHT 3kg | 6.6lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

Wall

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI

85

LIGHT OUTPUT

77 lm

Technical UL

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

Wall

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

**INSTALLATION REQUIRED**

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

LIGHT OUTPUT

77 lm

The Party Wall Lamp / Coco

Dimensions

18cm | 7.1"



11cm | 4.3"
22cm | 8.7"



Product

WIDTH 18cm | 7.1"

HEIGHT 22cm | 8.7"

DEPTH 11cm | 4.3"

WEIGHT NETTO 0.5kg | 1.1lbs

Packaging

WIDTH 31.5cm | 12.4"

HEIGHT 31.5cm | 12.4"

CUBAGE 0.02m³ | 0.72ft³

LENGTH 20.5cm | 8.1"

WEIGHT 3kg | 6.6lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

Wall

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



*Technical UL***MATERIAL**

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

COLOUR TEMPERATURE

2700 K (max)

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI

85

LIGHT OUTPUT

77 lm

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

LIGHT DIRECTION

Wall

LIGHT OUTPUT

77 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

The Party Wall Lamp / Glenn

Dimensions

17cm | 6.7"

10cm | 3.9"

22cm | 8.7"



Product

WIDTH 17cm | 6.7"**HEIGHT** 22cm | 8.7"**DEPTH** 10cm | 3.9"**WEIGHT NETTO** 0.5kg | 1.1lbs

Packaging

WIDTH 31.5cm | 12.4"**HEIGHT** 31.5cm | 12.4"**CUBAGE** 0.02m³ | 0.72ft³**LENGTH** 20.5cm | 8.1"**WEIGHT** 3kg | 6.6lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

220-240V

FREQUENCY

50/60

MAX POWER CONSUMPTION

6W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

COLOUR TEMPERATURE

2700 K (max)

CRI

85

LIGHT DIRECTION

Wall

LIGHT OUTPUT

77 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



*Technical UL***MATERIAL**

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

INSTALLATION REQUIRED

Yes

LIGHTSOURCE TYPE

LED

LIGHTSOURCE INCLUDED

Yes

NUMBER OF LIGHTSOURCES

1

INPUT VOLTAGE

110-120V

FREQUENCY

50/60

MAX POWER CONSUMPTION

6W

LAMPHOLDER

LED (Solid state)

LIFETIME

50000 hours

CABLE COLOUR

Black

CABLE LENGTH

15cm | 5.9"

COLOUR TEMPERATURE

2700 K (max)

CRI

85

LIGHT DIRECTION

Wall

LIGHT OUTPUT

77 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



The Party Wall Lamp / Ted

Dimensions

16cm | 6.3"



10cm | 3.9"
22cm | 8.7"



Product

WIDTH 16cm | 6.3"
HEIGHT 22cm | 8.7"
DEPTH 10cm | 3.9"
WEIGHT NETTO 0.5kg | 1.1lbs

Packaging

WIDTH 31.5cm | 12.4"
HEIGHT 31.5cm | 12.4"
CUBAGE 0.02m³ | 0.72ft³
LENGTH 20.5cm | 8.1"
WEIGHT 3kg | 6.6lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

Wall

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI

85

LIGHT OUTPUT

77 lm

Technical UL

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

Wall

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.**INSTALLATION REQUIRED**

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

LIGHT OUTPUT

77 lm

The Party Wall Lamp / Mayor

Dimensions

17cm | 6.7"**10cm | 3.9"****22cm | 8.7"**

Product

WIDTH 17cm | 6.7"**HEIGHT** 22cm | 8.7"**DEPTH** 10cm | 3.9"**WEIGHT NETTO** 0.5kg | 1.1lbs

Packaging

WIDTH 31.5cm | 12.4"**HEIGHT** 31.5cm | 12.4"**CUBAGE** 0.02m³ | 0.72ft³**LENGTH** 20.5cm | 8.1"**WEIGHT** 3kg | 6.6lbs

Technical CE

MATERIAL

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

COLOUR TEMPERATURE

2700 K (max)

LIGHT DIRECTION

Wall

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.

**INSTALLATION REQUIRED**

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

220-240V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CRI

85

LIGHT OUTPUT

77 lm

*Technical UL***MATERIAL**

Ceramic, Enogobio Finish, Alumminum, Brass knob

ENERGY LABEL

B

LIGHTSOURCE TYPE

LED

NUMBER OF LIGHTSOURCES

1

FREQUENCY

50/60

LAMPHOLDER

LED (Solid state)

CABLE COLOUR

Black

COLOUR TEMPERATURE

2700 K (max)

INSTALLATION REQUIRED

Yes

LIGHTSOURCE INCLUDED

Yes

INPUT VOLTAGE

110-120V

MAX POWER CONSUMPTION

6W

LIFETIME

50000 hours

CABLE LENGTH

15cm | 5.9"

CRI

85

LIGHT DIRECTION

Wall

LIGHT OUTPUT

77 lm

DIMMING & LIGHTING CONTROL

Mains, Trailing edge, Reverse phase

See last page for more information about the dimming possibilities.



Dimming & Lighting Control

Mains, Trailing edge, Reverse phase

The luminaire is dimmable by using an external Electronic Low Voltage dimmer. The dimmer is usually mounted on an existing wall socket and there is no need to change your home's wiring. On the dimmer it should show that it is a LED dimmer, suitable for 5 Watts or lower and C-type capable. Dimming is less fluent and can come with some flicker, a beep or a buzz.

Compatible models: Bert CE, Bert UL, Coco CE, Coco UL, Glenn CE, Glenn UL, Ted CE, Ted UL, Mayor CE, Mayor UL
